



Rugged 6.5" Flip-Down Video Display for Overhead Mounting

type number 00843



Main features:

- Rugged LCD-TFT color video monitor for use under harsh environmental conditions as in wheeled or tracked armoured military vehicles
- Mirrored or normal display for drivers rear, front and side view
- Video overlay marking for approximate vehicle width at distances of 1 m, 2 m, 3 m and 4 m
- Two video inputs for color and monochrome cameras or thermal imaging devices

Options:

- Display brightness and intensity of control element illumination switchable for day or night ambient light
- Night vision goggles compatibility
- RS485 data link (Can be delivered instead of discrete control inputs / outputs)
- CAN Version 2.0B (SAE J1939), protocol CANopen or CUP for advanced camera control and build in test

Optional accessories:

- various ruggedized cameras
- Wiring harness for various vehicles
- Video distribution box
- Digital video recorder

Ask for further technical information!

Functional or interface modifications can be realized on request. Each configuration change causes a new type number.

Technical Data:

Display type:	6,5" TFT LCD
Resolution:	1200 x 234 pixels (H x V)
Active display:	145 x 80 mm
Contrast ratio:	350:1
Brightness:	300 cd / m ²
Viewing angle:	50° horizontal / 35° vertical
Display windows:	Hardened, scratch resistant acrylic glass with anti-reflective and anti-fingerprint coating
Video inputs:	2 x CVBS according to CCIR / STANAG 3350B and NTSC / STANAG 3350C
Power inputs:	<ul style="list-style-type: none"> • 24 V DC / 10 W for display itself and camera power supply • 24 V DC / 12 W for camera heating both ref. to VG96916, (12 V DC Version available on request)
Power outputs:	<ul style="list-style-type: none"> • 12 V DC / 5 W for camera power supply • 24 V DC / 12 W loop through for camera heating
Control inputs:	reverse gear video overlay marking enable display & illumination enable day / night switch
Control outputs:	relay drive signal for camera washer pump or brush cleaning
Controls:	contrast, brightness, camera selection, camera cleaning
Connectors:	VG 96912
EMI:	VG 95373 (MIL-STD-461E on request)
Protection:	IP 54
Temperature:	-32 °C to +85 °C (operating) -40 °C to +90 °C (storage)
Dimensions:	280 x 55 (160 if open) x 162 mm (W x H x D)
Weight:	approx. 2 kg
Color:	Titan silver