



Not recommended for new design!

Ruggedized 6,5" Display Unit for Vehicle Day & Night-Vision Application

type number 00741 | 01077



Description:

The video displays of the RDU06 series have been designed for rough military environment.

Color or monochrome cameras, compliant with PAL- or NTSC- standard, can be connected.

Due to the high resolution, the RDU06 provides photo realistic picture quality of almost 16 million colors and excellent contrast with night vision pictures.

The tight and extremely stable enclosure of the RDU06 series complies with IP 65 requirements. Improved thermal design guarantees operation at high ambient temperatures.

Technical Data:

Display type:	6.5" TFT W.LED backlight
Resolution:	XGA 1024 x 768 pixels
Standard:	PAL; NTSC
Colors:	16 millions
Grey scales:	256, 8 bit
Power supply:	24 V DC (18 V DC to 32 V DC) according to VG 96916-5
Environmental conditions:	according to MIL-STD-810F
Protection:	IP 65 according to EN 60529
Operating temperature:	-20 °C to +55 °C
Dimensions:	226 x 150 x 65 mm (W x H x D)
Controls:	brightness and contrast
Special features:	built for mobile ground applications



type number 01077 Option with:

- Internal heater for -32 °C operation
- Buffered video output
- On / off push button
- EMI front filter plate
- Pressure differential valve
- Paint finish RAL1013 or TBD.

Ask for further technical information!

Functional or interface modifications can be realized on request. Each configuration change causes a new type number.

Technical Data:

Display type:	6.5" TFT W.LED backlight
Resolution:	XGA 1024 x 768 pixels
Standard:	PAL; NTSC
Colors:	16 millions, 24 bit
Grey scales:	256, 8 bit
Power supply:	24 V DC (18 V DC to 32 V DC) < 15 W / < 50 W with heating according to VG 96916-5
Environmental conditions:	according to MIL-STD-810F
Protection:	IP 65 according to EN 60529
Operating temperature:	-32 °C to +55 °C with integrated heating
Dimensions:	226 x 150 x 65 mm (W x H x D)
Controls:	On / Off; brightness and contrast