

## DC / DC Power Supplies 12 Vdc Output

type numbers: 00791 | 00845  
00846 | 00847



type number  
00791 +  
00845



type number  
00846 +  
00847

type number 00791 + 00846

Input voltage:	18,0 Vdc to 36,0 Vdc
Consumption:	0,05 to 5,0 A at 24 Vdc
Output voltage:	12,0 Vdc
Output current:	8,0 A
Connector in / out:	SJT/PG (type number 00791) SJT/SJT (type number 00846)

type number 00845 + 00847

Input voltage:	11,0 Vdc to 36,0 Vdc
Consumption:	0,05 to 2,5 A at 24 Vdc
Output voltage:	12,0 Vdc
Output current:	4,0 A.
Connector in / out:	SJT/PG (type number 00845) SJT/SJT (type number 00847)

Ask for further technical information!  
Functional or interface modifications can be realized on request. Each configuration change causes a new type number.

### Description:

This family of DC / DC power supplies is designed for automotive applications to be used under harsh environmental conditions.

### Mechanical Specifications:

Material:	Aluminium
Dimensions:	194 x 101 x 40 mm (W x D x H)
Weight:	approx. 1 kg
Ground terminal:	M8
Finish / colour:	Powder coating, green RAL 6031 HR or TBD
Protection:	IP 66 (EN 60529)

### Electrical Data:

Input according to:	VG 96916 -5
Voltage accuracy:	±1,0 % max
Temperature coefficient:	±0,05 % /°C max
Ripple & noise, 20MHz BW:	60 mV RMS
max.:	150 mV pk-pk
Safety according to:	EN 60950-1
EMC / EMI:	MIL-STD-461E or TBD

### Environmental Data (acc.to MIL-STD-810F):

Temperature:	-40 °C to +85 °C (operating) -46 °C to +90 °C (storage)
Humidity:	0 % to 100 % rel.
Vibration.:	Fig. 514.5C3 for wheeled vehicles
Shock:	10 x 10 g / 6 ms

### Option:

Remote control for electronically switch on and off.