

type number 00727



Description:

- This 15" TFT Monitor was developed for application under harsh environmental conditions. It can be used for industrial applications as well as for mobile land vehicles.

Special performances:

- Extended temperature range by improved thermal design
- Improved vibration and shock performance in accordance to MIL/VG and EN
- Front panel and operational elements are water resistant
- Low loss power converter
- Contrast improving anti-glare and EMI protecting front glass

Adjustments are supported by OSD by 4 push-buttons located on the front panel (protected by a cover plate)

Options:

- Resistive Touch-Screen
- Power supply 100 Vac to 230 Vac
- Extended operating temperature range from -20 °C to +56 °C

Ask for further technical information!
Functional or interface modifications can be realized on request. Each configuration change causes a new type number.

Technical Data:

Resolution:	XGA 1024 x 768 pixels
Display standards:	VGA 640 x 480 pixels
	SVGA 800 x 600 pixels
	XGA 1024 x 768 pixels
	TEXT 720 x 400 pixels
	MAC 832 x 624 pixels
Synchronization:	TTL high or low active C-Sync, Sync on Green
Colours:	Full Colour
Connectors:	15 pin HD VGA socket line connector TBD
Power supply:	18 Vdc - 32 Vdc 230 Vac (optional)
Protection:	front panel IP 65
Temperature:	-10 °C to +56 °C (operation) -20 °C to +70 °C (storage)
Dimensions:	432 x 343 x 80 mm (W x H x D)